Epson TM-C3400

DATASHEET





The TM-C3400 prints on a wide range of labels, tickets and wristbands

Print labels, tickets and wristbands on demand with the Epson TM-C3400. Its colour printing capabilities improve identification, helping prevent critical errors in a number of applications, such as wristbands and prescription labels for healthcare.

Printing custom designs on demand reduces costs associated with pre-printing, including stock management and wastage. The TM-C3400 offers additional savings with a new economy print mode for users with low print volumes.

This highly versatile printer is compatible with a wide range of matte and glossy media between 30 and 112mm wide. The resulting prints are long-lasting, as Epson's DURABrite Ultra pigment ink resists smudging, fading, water and most other liquids. Another benefit of inkjet technology is improved security, as thermal transfer ribbons can carry imprints of sensitive information. With a print speed of up to 92mm/sec and an integrated auto-cutter, printing 100 labels takes less than three minutes, making the TM-C3400 ideal for busy environments. Mis-prints are avoided with Epson's automatic nozzle checking technology (AID), which senses and fixes nozzle clogs or dead pixels in barcodes. Productivity is further enhanced with the printer's robust design for reliable operation.

The TM-C3400 is controlled from the front, making it easier to use and allowing installation under desktops to save counter space. Integration is straightforward with direct control and programming from within applications. For a quick start, the TM-C3400 is also available in a version with basic label design software.

KEY FEATURES

- Full colour label printer with long lasting DURABrite Ultra pigment ink
- Unique high-speed colour printing (100 labels in less than 3 minutes, including cutting)
- High capacity ink cartridge for easy replacement
- Variable paper width: 30-112mm
- Suitable for various print media such as labels, papers and wristbands
- Rear paper feed
- Front operation panel enables installation under desktops and surfaces
- Integrated autocutter
- Extremely low energy consumption



Simple paper loading



Front controls for easy operation



Space saving design



PRODUCT SPECIFICATIONS

PRINT METHOD MicroPlezo serial inkjet PRINT RESOLUTION \$80dpi x 180dpi 720dpi x 380dpi 720dpi x 380dpi PRINT SPEED \$2mm/s (printing width 56mm, 380dpi x 180dpi, bi-directional printing) 82mm/s (printing width 72mm, 380dpi x 180dpi, bi-directional printing) PRINT FONTS Printa all types of true type fonts and graphics BARCODES Available through the EPSON Windows driver: Baroodes: UPC-A, UPC-E, UAN13(EAN), UAN8(EAN), Code39, ITF, Codabar, Code33, Code128, GS1-128, GS1-128, GS1-1					
380dopi x 380dopi PRINT SPEED 92mm/s (printing width 56mm, 360dopi x 180dopi, bi-directional printing) 82mm/s (printing width 72mm, 360dopi x 180dopi, bi-directional printing) 82mm/s (printing width 72mm, 360dopi x 180dopi, bi-directional printing) PRINT FONTS Prints all types of true type fonts and graphics BARCODES Available through the EPSON Windows driver: Barcodes: UPC-A, UPC-E, JUN3(EAN), JN8(EAN), N06(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Comidirectional, GS1 DataBar Tuncated, GS1 DataBar Limited, GS1 DataBar Expanded 2-dimensional codes: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Composite Symbology, DataMatrix, Aztec PAPER TYPE Paper, Label, Synthetic Label, Wristbands PAPER WIDTH 30mm – 120mm PRINTING WIDTH Max. 104mm INK CARTRIDGE SJIC 15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mol lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MAcrosoft Windows 2PO SP4 (32 bit)	PRINT METHOD	MicroPiezo serial inkjet			
B2mm/s (printing width 72mm, 360dpi × 180dpi, bi-directional printing) PRINT FONTS Prints all types of true type fonts and graphics BARCODES Available through the EPSON Windows driver: Barcodes: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded 2-dimensional codes: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, QS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Composite Symbology, DataMatrix, Aztec PAPER TYPE Paper, Label, Synthetic Label, Wristbands PAPER FORMAT Continuous paper and labels, die-cut labels (Paper position detection with sensors for black-marks and gaps between labels) PAPER WIDTH 30mm – 120mm PRINTING WIDTH Max. 104mm INK CARTRIDGE SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) Wicrosoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP3 (22 bit)(4 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Ser	PRINT RESOLUTION	360dpi x 360dpi			
BARCODES Available through the EPSON Windows driver: Barcodes: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code33, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Expanded 2-dimensional codes: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Composite Symbology, DataMatrix, Aztec PAPER TYPE Paper, Label, Synthetic Label, Wristbands PAPER FORMAT Continuous paper and labels, die-cut labels (Paper position detection with sensors for black-marks and gaps between labels) PAPER WIDTH 30mm – 120mm PRINTING WIDTH Max. 104mm INK CARTRIDGE SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP3 (23 bit) Microsoft Windows Server 2003 RP2 (32 bit/64 bit)	PRINT SPEED				
Barcodes: UFC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Itmited, GS1 DataBar Expanded 2-dimensional codes: PDF417, OR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked, Omnidirectional, GS1 DataBar Expanded Stacked, Composite Symbology, DataMatrix, Aztec PAPER TYPE Paper, Label, Synthetic Label, Wristbands PAPER FORMAT Continuous paper and labels, die-out labels (Paper position detection with sensors for black-marks and gaps between labels) (PAPER WIDTH 30mm – 120mm PRINTING WIDTH Max. 104mm INK CARTRIDGE SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows VSta SP2 (32 bit/64 bit) Microsoft Windows VSta SP2 (32 bit/64 bit) Microsoft Windows VSta SP2 (32 bit/64 bit)	PRINT FONTS	Prints all types of true type fonts and graphics			
PAPER FORMAT Continuous paper and labels, die-cut labels (Paper position detection with sensors for black-marks and gaps between labels) PAPER WIDTH 30mm – 120mm PRINTING WIDTH Max. 104mm INK CARTRIDGE SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows XP SP3 (32 bit) Microsoft Windows SP SP3 (32 bit) M	BARCODES	Barcodes: UPČ-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded 2-dimensional codes: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked			
Image: Construction of the constend of the construction of the construction	PAPER TYPE	Paper, Label, Synthetic Label, Wristbands			
PRINTING WIDTH Max. 104mm INK CARTRIDGE SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows XP SP3 (32 bit) Microsoft Windows SP SP3 (32 bit)/ Microsoft Windows SP SP3 (32 bit)/ Mi	PAPER FORMAT				
INK CARTRIDGE SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink) INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows XP SP3 (32 bit) Microsoft Windows SP2 (32 bit/64 bit) Microsoft Windows SP2 (32 bit/64 bit), Microsoft Windows Server 2008 R2	PAPER WIDTH	30mm – 120mm			
INTERFACES USB 2.0 or Ethernet IEEE 802.3 POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows SP SP3 (32 bit) Microsoft Windows SP SP2 (32 bit/64 bit) Microsoft Windows SP SP2 (32 bit/64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	PRINTING WIDTH	Max. 104mm			
POWER SUPPLY Embedded AC adapter (PS-180) POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows SP2 (64 bit) Microsoft Windows SP2 (23 bit/64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2003 SP2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	INK CARTRIDGE	SJIC15P (CMY 3-color combined, DuraBrite Ultra pigment Ink)			
POWER CONS. Operating: approx. 26W standby: approx. 5W RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 R2 SP2 (32 bit/64 bit)	INTERFACES	USB 2.0 or Ethernet IEEE 802.3			
RELIABILITY MTBF: 75,000 hours, MCBF: 9.8 mio lines AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Vista SP2 (32 bit/64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	POWER SUPPLY	Embedded AC adapter (PS-180)			
AUTOCUTTER Full cut autocutter included DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	POWER CONS.	Operating: approx. 26W standby: approx. 5W			
DIMENSIONS (WxDxH) MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows Server 2003 R2 SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2003 SP2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit), Microsoft Windows Server 2008 SP2	RELIABILITY	MTBF: 75,000 hours, MCBF: 9.8 mio lines			
MASS EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2003 SP2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	AUTOCUTTER	Full cut autocutter included			
EMC STANDARDS VCCI class B, FCC class B, CE marking SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2003 SP2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	DIMENSIONS (WxDxH)				
SAFETY STD. UL / CSA / TÜV (EN60950-1) OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	MASS				
OPERATING SYSTEMS Microsoft Windows 2000 SP4 Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit)	EMC STANDARDS	VCCI class B, FCC class B, CE marking			
Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Vista SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit), Microsoft Windows Server 2008 R2	SAFETY STD.	UL / CSA / TÜV (EN60950-1)			
	OPERATING SYSTEMS	Microsoft Windows XP SP3 (32 bit) Microsoft Windows XP SP2 (64 bit) Microsoft Windows Server 2003 R2 SP2 (32 bit/64 bit) Microsoft Windows Vista SP2 (32 bit/64 bit) Microsoft Windows Server 2008 SP2 (32 bit/64 bit), Microsoft Windows Server 2008 R2			



WHAT'S IN THE BOX

- TM-C3400 label printer
- Ink cartridge (SJIC15P)
- Sample label roll
- USB cable (with the USB model only)
- Paper ejection tray
- Instruction sheet
- User's manual
- Power switch cover

OPTIONS

- Warranty extension
- Ink cartridge (SJIC15P)

LINSON		
	 10.100	



LOGISTICS

	Epson TM-C3400 printer	Epson SJIC15P cartridge	Epson inkjet matte label		
SKU code	USB:		76mm label width (continous roll)	1516052	
	Ethernet:		105mm label width (continous roll)	1516054	
Min. order quantity / per carton	1/1	1/10	76mm width: 105mm width:	18/18 12/12	
Carton weight		(10 cartridges)	76mm width: 105mm width:		
Carton dimensions (WxDxH)		(10 cartridges)	76mm width: 105mm width:		

*including basic label design software CD



For further information please contact your local Epson office or visit www.epson-europe.com

For further information please contact your local Epson office or visit www.epson-europe.com Austria 0810/20 01 13 (0,07 ¢/min) Belgium 070/350120 (0,1735 ¢/min) Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04 (Cost of local call, operator charges may apply) Germany 01805/23 41 10 (0,14 ¢/min aus dem dt. Festnetz, Mobilfunkpreise abweichend, Ab 1.3.2010 Mobilfunkpreis max. 0,42 ¢/min) Greece 210-8099499 Hungary 06800 147 83 Ireland 01 436 7742 Italy 02-660321 10 (0,12 ¢/min) Luxembourg 900/43010 (0,24 ¢/min) Middle East +9714 8818934 Netherlands 8000-5050808 (0.05 ¢/oproep + 0.15 ¢/min) Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 z/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtal – 0,30 kr/min, Utlandssamtal – 0,89 kr/min) Switzerland 0848 448820 (8 cent./min) Turkey (0212) 3360303 United Kingdom 0871 222 6702

EPSON

